




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 17/39		A2	(11) International Publication Number: WO 99/59486
			(43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/US99/11164		(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 20 May 1999 (20.05.99)			
(30) Priority Data: 09/082,047 20 May 1998 (20.05.98) US		Published <i>Without international search report and to be republished upon receipt of that report.</i>	
(71) Applicant: NEW ENGLAND MEDICAL CENTER [US/US]; 750 Washington Street, Boston, MA 02111 (US).			
(72) Inventors: WANG, Paul, J.; 209 Middlesex Road, Chestnut Hill, MA 02467 (US). RASTEGAR, Hassan; 102 Garland Road, Newton, MA 02159 (US).			
(74) Agent: MOORE, Ronda, P.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).			

(54) Title: A CARDIAC ABLATION SYSTEM AND METHOD FOR TREATMENT OF CARDIAC ARRHYTHMIAS AND TRANS-MYOCARDIAL REVASCULARIZATION

(57) Abstract

A medical device, and related method, use epicardial ablaters and detectors for intraoperative epicardial approaches to ablation therapy of cardiac conduction pathways. An epicardial gripper is sized to grasp the cardiac circumference or smaller structures on the epicardial surface of the heart. Ablators are disposed on the arms of the gripper for epicardial ablation of cardiac conduction tissue. In another embodiment of the invention, an electrode system includes a flexible, adjustable probe forming a loop for epicardial ablation. Ablators are provided on one or multiple surfaces



of the probe for epicardial ablation of cardiac conduction tissue. In yet another embodiment of the invention, an endocardial ablator detection system provides an indicator adjacent an ablator on an endocardial catheter, and a detector on an epicardial probe. The epicardial probe detects signals transmitted by the indicator on the endocardial catheter to localize the position of the endocardial ablator relative to the epicardial surface. The surgeon uses this information for guidance in adjusting the position of the endocardial ablator according to therapeutic objectives of cardiac ablation.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A CARDIAC ABLATION SYSTEM AND METHOD
FOR TREATMENT OF CARDIAC ARRHYTHMIAS AND
TRANSMYOCARDIAL REVASCULARIZATION

Background of the Invention

Tachycardia is a type of cardiac arrhythmia and is a serious, often-times, fatal condition characterized by rapid, uncontrolled, and ineffective beating of the heart. Most tachycardia is one of two broad categories: ventricular tachycardia (hereinafter VT) and supraventricular tachycardia (hereinafter SVT). VT occurs in the lower chambers of the heart, the ventricles, and frequently leads to serious complications, including sudden cardiac death. Atrial fibrillation and flutter, forms of SVT, originate in the upper chambers of the heart, the atria, and often result in chest pain, fatigue and dizziness and, while generally not life-threatening, is a leading cause of stroke in the United States.

Currently, many cases of VT and SVT are treated by drugs that modify the electrical characteristics of the heart tissue. However, the drugs do not eliminate or may not completely control the arrhythmia. In many cases of sustained VT, implantable cardiac defibrillators are used which deliver powerful shocks to the heart when fibrillation is detected. Concurrent treatment with drugs is standard therapy and each implantation of a cardiac defibrillator, of which there may be more than one per patient, is very expensive.

Some forms of SVT are treated by endocardial ablation, a minimally invasive procedure. During endocardial ablation, a mapping catheter is passed through an artery or vein into the patient's heart to find the site(s) of the arrhythmogenic tissue, the tissue from which the tachycardia originate. This same catheter or a separate catheter is used to transmit sufficient energy to thermally damage the tissue either by heating or cooling. (FIG. 1)

- 2 -

In atrial fibrillation the regular pumping action of the atria is replaced by a disorganized, ineffective quivering caused by chaotic conduction of electrical signals through the upper chambers of the heart. Although not immediately life threatening, atrial fibrillation may cause up to a 30% reduction in cardiac output and can lead to more serious conditions, including the formation of blood clots in the atria that can dislodge and travel to the brain resulting in stroke. Currently, the only curative treatment for atrial fibrillation is the surgical "maze procedure", an open heart procedure in which the surgeon makes several incisions in the right and left atria creating scar tissue to electrically separate portions of the atria. Despite clinical success of the maze procedure, it is time-consuming and demanding. The procedure requires open heart surgery and is very expensive. Accordingly, only a modest number of maze procedures are performed annually in a limited number of centers.

Another use of ablation technology, either endocardial or epicardial, is transmyocardial revascularization. The creation of small ablation holes results in genesis of new blood vessels, providing a source of blood flow in areas of the heart not receiving sufficient blood.

The present invention provides another apparatus and method for treating cardiac arrhythmia, that may be widely applicable. The present invention also provides an apparatus for transmyocardial revascularization.

Summary of the Invention

The present invention provides devices and methods for epicardial and endocardial approaches for myocardial ablation for treatment of cardiac arrhythmias and myocardial revascularization.

One aspect of the invention provides a gripper for grasping the epicardial surface of the

- 3 -

heart for the purpose of ablating cardiac tissue. In one embodiment, the arms of the gripper are sized and dimensioned to substantially encircle the circumference of the heart or a portion of it, thereby stabilizing the gripper against the contracting heart. The ablaters are sized and positioned on one or more of the arms of the gripper according to the location and geometry of the cardiac tissue to be ablated.

In another embodiment, the gripper is sized and dimensioned to encompass structures on the surface of the heart. In yet another embodiment of this aspect of the invention, one arm of the gripper is inserted through an incision in the wall of the heart into one of the heart chambers. The other arm or arms of the gripper are positioned on the epicardial surface to stabilize the heart. The ablaters are located on an arm or arms in an array according to the location and geometry of the tissue to be ablated. In one embodiment, the gripper ablates both the epicardial and endocardial surfaces.

In one embodiment, one or more of the arms may form an array. One embodiment of the array is a Y. Another embodiment of the array are loops or spokes.

Another aspect of the invention is an electrode system comprising a probe in the form of an adjustable, flexible substrate forming a substantially closed loop for epicardial ablation. In one embodiment of the invention, the loop is sized to substantially encompass a structure on the epicardial surface of the heart. In another embodiment, the loop is substantially sized to encircle the circumference of the heart. The cross section of the probe may be round, oval, multifaceted or have multiple radii. In one embodiment the probe does not encompass the entire circumference of a portion of the heart.

In another embodiment of this aspect of the invention, the size of the substantially closed loop comprising the probe is adjustable by a pull string attached to one end of the probe. In another embodiment the probe substrate comprises an elastomeric material. The loop of the

- 4 -

elastomeric probe is adjustable by expanding or contracting the probe.

In another embodiment of this aspect of the invention, the electrode system is sized and dimensioned for insertion through an endoscope or thoracoscope. In yet another embodiment, the electrode system includes attachments such as, for example, a cooling system in
5 communication with the probe or a gripping device such as a suction device in communication with the probe.

In one particular embodiment of the invention, the electrode system comprises a glove and an ablator in communication with one or more fingers of the glove.

The ablaters of the electrode system are positioned generally to correspond to the cardiac
10 tissue to be ablated. In one embodiment, the ablaters are positioned on the inner surface of the probe. In another embodiment, the ablaters are positioned on more than one surface of the probe. For example, the ablaters may be positioned on the flat surface of a probe with a D-shaped cross section, on one semi-circle of a circular cross section, or on one or more surfaces of a rectangular cross section. The ablaters may be located on one or more arms in any
15 configuration.

In a preferred embodiment of this aspect of the invention, the ablaters may be individually and independently activated. In another particular embodiment, the ablaters are removably attached to the probe substrate.

Another aspect of this invention comprises an endocardial ablator-detection and ablation
20 system for performing transmural ablation. The ablator-detection and trans-mycardial ablation system provides an indicator located on an endocardial ablating catheter adjacent an ablator, and a detector located on an epicardial probe. The indicator located on the endocardial ablating catheter transmits a signal indicating the position of the ablator on the catheter. The epicardial detector receives the signal thereby localizing the relative epicardial position of the

- 5 -

ablator on the endocardial catheter. Ablating energy is applied when the ablator is appropriately positioned.

In one embodiment of the endocardial ablator detection system, the indicator is a magnet and the detector is a magnetic field detector. In another embodiment of the detection system, the indicator is a light transmitter, such as, for example, laser light, and the epicardial detector comprises a light detector. In another embodiment of the system the indicator is a light source emitting fluorescent light and the epicardial detector detects light in the wavelength of fluorescence. In yet another embodiment of the invention, the epicardial detector comprises an ultrasound detector, or an echocardiograph. In yet another embodiment, a magnet in the epicardial probe attracts a magnetic or metallic element in the endocardial ablator, guiding the ablaters into position.

In any aspect of the invention, cooling or ablating energy may be applied by the ablaters to ablate cardiac tissue. In one embodiment, cooling fluid travels via a lumen in the ablator and exits via small holes carrying the fluid through another lumen that exits from the catheter. The change in pressure or phase change results in cooling or freezing. The ablating energy applied to ablate cardiac tissue in any aspect of the invention may be thermal, radio frequency, direct current, ultrasound or laser energy.

Brief Description of the Drawings

FIG. 1 is a simplified and diagrammatic sagittal section view of the interior of the left side of the heart showing an endocardial ablating catheter of the prior art within a large vessel and left atrium;

FIG. 2A is a simplified and diagrammatic view of the anterior surface of the left heart and FIG. 2B is a simplified and diagrammatic view of the posterior surface of the right heart;

FIG. 3 is a view of an epicardial gripper with two moveable arms and ablaters on both

- 6 -

arms;

FIG. 4 is a view of an epicardial gripper with one moveable arm with ablaters and one fixed arm;

FIG. 5A is a diagrammatic view of another embodiment of the epicardial gripper with
5 one moveable arm and one fixed arm;

FIG. 5B is an enlarged view of a serrated surface of the ablator;

FIG. 6 is a diagrammatic view of another embodiment of the epicardial gripper with one moveable arm and two fixed arms and ablaters on the inner surface of all arms;

FIG. 7A is a diagrammatic view of another embodiment of an epicardial gripper with two
10 moveable curvilinear arms;

FIG. 7B is a diagrammatic view of another embodiment of an epicardial gripper with two moveable arms in a Y-shaped array;

FIG. 7C is a diagrammatic view of another embodiment of an epicardial gripper with two loop-shaped arms;

15 FIG. 7D is a diagrammatic view of another embodiment of an epicardial gripper with two multi-element spokes as arrays;

FIG. 8 is a diagrammatic view of another embodiment of an epicardial gripper with two moveable arms and ablaters on one of the two moveable arms;

FIG. 9 is a diagrammatic view of another embodiment of an epicardial gripper with
20 multiple ablaters disposed on the inner surface of both arms of the gripper;

FIG. 10A-J is a cross sectional diagrammatic view of the various arrays of ablaters on the surface of the arm of the epicardial gripper or the surface of the probe of the electrode system;

FIG. 11A is a diagrammatic view of multi-element cooling ablaters in a portion of the arm of the gripper;

- 7 -

FIG. 11B is a diagrammatic view of another embodiment of the cooling ablaters;

FIG. 12A is a diagrammatic view of laser ablaters in a portion of the arm of the gripper;

FIG. 12 B is another embodiment of laser ablaters wherein the ablaters are lenses in the arm of the gripper attached by optical fibers to a laser source;

5 FIG. 12C is another embodiment of laser ablation wherein the ablaters are optical fibers connected to a laser source;

FIG. 13 is a diagrammatic view of the adjustable, flexible probe substantially forming a loop of the electrode system;

FIG. 14A is a diagrammatic view of the adjustable, flexible probe substantially
10 encompassing an auricle of the heart;

FIG. 14B shows a camera permitting visualization of the cardiac surface;

FIG. 15 is a diagrammatic view of the surface of the probe with the ablaters arranged in a linear array;

FIG. 16A-B is a diagrammatic view of cooling ablaters in a portion of the probe of the
15 electrode system;

FIGS. 17A is a diagrammatic view of laser ablaters in a portion of the probe of the electrode system;

FIG. 17B is another embodiment of laser ablaters wherein the ablaters are lenses in the probe of the electrode system attached by fiber optics to a laser source;

20 FIG. 17C is another embodiment of laser ablation wherein the ablaters are optical fibers connected to a laser source;

FIG. 18A is a diagrammatic view of the pull-string adjustable flexible probe of the electrode system in open position;

FIG 18B is a diagrammatic view of the pull-string flexible probe of the electrode system

- 8 -

in closed position;

FIG. 18C is another embodiment of the pull-string flexible probe;

FIG. 19 is a diagrammatic view of the adjustable, flexible probe made of elastomeric materials;

5 Fig. 20 is a diagrammatic view of the spring-adjustable flexible probe of the electrode system;

FIG. 21 is a cross-sectional view of the myocardium and endocardial ablator detection system;

10 FIG. 22 is a cross-sectional view of the myocardium and a endocardial laser ablator detection system;

FIG. 23 is a cross-sectional view of the myocardium and an epicardial ultrasound imaging probe.

Description

Anatomy of the Heart

15 The heart as shown in FIG. 1 has at least two surfaces, an outer surface, the epicardium 20, and an inner surface, the endocardium 22. Numerous cardiac structures are identifiable on the epicardial surface 20. For example, as illustrated in FIGS. 2A and B, the pulmonary artery 24 and aorta 26 exit from the epicardial surface 20 at the base 28 of the heart. The apex 30 of the heart is the pointed end of the heart opposite the base 28 of the heart. The left atrium 32 and
20 right atrium 34 are readily identifiable by the left 36 and right 38 auricles. The right ventricle 40 and left ventricle 42 are localized by identifying the left longitudinal groove 44 which runs from approximately the heart base 28 to apex 30 on the epicardial surface 20. The coronary groove 46

- 9 -

on the epicardial surface 20 separates the cardiac atria 32, 34 from the cardiac ventricles 42, 40. The great coronary vessels 48 are disposed in the coronary groove 46.

The endocardium 22 lines the inside walls of both types of heart chambers, i.e., the atria and the ventricles as illustrated in FIG. 1. The endocardial surface 22 opposes the epicardial surface 20 and is separated by the thick muscular wall of the heart, the myocardium 50.

In one aspect of the invention as shown in FIG. 3, an epicardial gripper 52 includes at least two arms 54 that pivot around each other at a pivot point 56. The arms 54 of the gripper 52 are each attached to a respective handle 58. In one embodiment as shown in FIG. 3 the arms 54 are moveable relative to each other. In another embodiment shown in FIGS. 4 and 5, the gripper 52 may include two arms wherein one arm is a moveable arm 60 and the remaining arm is a fixed arm 62, relative to the moveable arm. The arms may be disposed at the end of a long barrel 59, for example as illustrated in FIG. 5. In another embodiment, in a multi-arm gripper, one or more arms 62 are fixed while the opposing one or more arms 60 is moveable as shown in FIG. 6. Any number of arms is contemplated, at least one of which is moveable.

In one embodiment, as illustrated in FIG. 5B, the ablation surface, non-ablation elements in contact with the heart tissue or both are serrated or irregular in contour to increase friction.

As shown in FIGS. 3-9, the arms 54 of the gripper 52 generally comprise an elongate body pre-formed into a generally curved or curvilinear shape. The shape corresponds to the geometry of the epicardial surface to be ablated.

The arms of the gripper are formed from an electrically non-conductive, inert, material. Suitable materials for the arms include, but are not limited to, Pebax®, polyethylene, or polyester. Other materials, with the above characteristics, which retain their shape at body temperature are also contemplated. The gripper may be formed of shape memory materials, for example, nitinol. The gripper may be enclosed within a sheath dimensioned for insertion

- 10 -

through a small orifice. After the gripper is inserted, the sheath is removed and the gripper arms assume a pre-formed shape.

Each of the arms of the gripper 52 have an inner surface 64 and an outer surface 66 defining a cross section. The cross section may be substantially circular, semi-circular, rectangular, V-shaped, D-shaped or the cross-section may have multiple radii as illustrated in FIGS. 10A-J. In one embodiment, ablaters 68 may be positioned on the inner surface 64 as shown in FIGS. 3-9. Ablators ablate cardiac tissue. Ablation destroys or removes the function of tissue. In some cases ablation is followed by revascularization of the cardiac tissue. As shown in cross section in FIG. 10, in other embodiments the ablaters are disposed on one or more surfaces of one or more arms. In various embodiments, as illustrated in FIGS. 3-9, ablaters are positioned on one or more moveable arms, one or more fixed arms, or both.

Ablators may be positioned on the arms in a variety of ways. In one embodiment, the ablator is a single, linear ablator as shown in FIGS. 3-8. In another embodiment, multiple ablaters may be arranged on the arms in a patterned array, such as, for example, a linear array as illustrated in FIG. 9. The spacing of the ablaters depend on the geometry of the tissue to be ablated. The number of ablaters and the dimensions of individual ablaters may be determined by tissue geometry, the arm shape, and the requirement for arm flexibility. In one embodiment, each ablator is preferably made of platinum, about 0.2-5 mm thick and about 1-5 mm long. In another embodiment, the platinum is preferably 2 mm thick and preferably about 4 mm long. In yet another embodiment, the ablaters comprise detachable, reattachable ablaters.

In one embodiment, prior to securing the ablaters to the arms, each of the ablaters is attached to a low resistance conductor wire threaded through holes in the arm. In one embodiment, the ablating energy in each ablator is individually controllable.

In another embodiment of the gripper as shown in FIG. 11A, the ablaters 68 are cooling

- 11 -

elements as known to one skilled in the art. The arms 54 of the gripper 52 have an interior lumen 72, the proximate end 74 of the lumen 72 in communication with a connection port (not shown) in the handle 58. The lumen 72 communicates with a hollow cavity 78 formed in the ablator 68. In FIG. 11B, inlet holes 69 connect the incoming fluid to a lower pressure object.

5 Cooling may be accomplished by the delivery of a fluid or gas to the ablators 68 contained within the gripper arms. The cooling fluid may recirculate or exit via small holes in the arms. Cooling is achieved by delivering fluid or gas to the arms via one or more tubes. The gas may exit via one or more tubes. The fluid or gas may come in direct contact with the ablators or be separated from the ablators by a surface.

10 The cryoablation gripper device may consist of one or more elements consisting of a delivery tube for the entrance of the cryogen. As shown in FIG. 11B, there are one or more small orifices 69 at the ablation surface. At these orifices the cryogen goes from a high to low pressure creating the cooling. These may or may not be a pressure change only or a phase change (FIG. 11B). There may be one or more delivery tubes 74 and one or more tubes 75 that take the fluid
15 or gas back to the proximal end.

In another embodiment, the ablators are lasers. In one embodiment shown in FIG. 12A, the laser ablators 80 are disposed along the inner surface 64 of an arm 54 in an array, such as a linear array. The lasers 80 are attached to conductor wire 82 leading to an energy source 84. In another embodiment shown in FIG. 12B the laser ablators are lenses 86 attached by fiber optics
20 88 to a laser source 84. In another embodiment shown in FIG. 12C the laser ablators are optical fibers 88 attached to a laser source 84. In another embodiment (not shown) the ablator is an ultrasound transducer.

The gripper may have one or more suction elements. The suction device consists of a small hole which is along the contact surface of the gripper. This hole is attached to a tube

- 12 -

which exits from the gripper. Suction is achieved by creating negative pressure within this tube using an apparatus outside the body. In another embodiment these suction elements consist of suction cups which create suction when contact pressure is applied.

In a preferred embodiment shown in FIG. 8, the gripper 52 comprises two moveable arms 5 60 configured to act as a clamp. A linear array of continuous or discontinuous ablation elements or a single continuous linear ablator 68 is located on one arm 60. In clinical use, the arms 60 are disposed about the circumference of the heart on the epicardial surface. The arm with the one or more ablators is aligned such that the ablator is positioned over the tissue to be ablated. The opposing arm without ablators is disposed on the opposite side of the heart to stabilize the 10 gripper on the epicardial surface. In one embodiment, when the alignment of the ablating arms with the myocardial tissue to be ablated is satisfactory as known by a skilled artisan, ablating energy is applied. Sufficient ablating energy is applied to the ablators to ablate cardiac tissue as required.

In an alternate embodiment (not shown), the gripper comprises an ablating arm and a 15 non-ablating arm. The ablating arm is inserted through an incision made by a surgeon through the wall of the heart. The ablating arm is aligned with the region of the endocardial surface to be ablated and the non-ablating arm is disposed on the epicardial surface to stabilize the gripper. When the ablating arm is aligned by the surgeon with the endocardial surface to be ablated, sufficient ablating energy is supplied to the ablators to ablate the cardiac tissue as desired.

20 The gripper device is designed to ablate cardiac tissues. The gripper is able to maintain stable contact with the epicardial surface by partially or completely encompassing a circumference of a part of the heart. The ablation may be performed on any portion of the epicardial surface with which the gripper has contact. The ability of the gripper to partially or completely encompass a circumference of a part of the heart creates stability and allows for

- 13 -

contact by conforming to the epicardial surface of the heart. Ablation may be performed in a linear or curvilinear arrangement.

In another embodiment, the invention is an electrode system for epicardial ablation of cardiac tissue. As illustrated in FIG. 13 the electrode system 90 comprises a handle 58.

5 Attached to one end of the handle 58 is a probe 92 comprised of an adjustable, flexible substrate forming a substantially closed loop. The loop is sized to substantially encompass a structure of the heart such as an auricle 38 as shown in FIG. 14. The probe 92 has at least one contact surface. At least one ablator 68 is positioned on at least one contact surface.

10 In one embodiment of the gripper, an ultrasound probe is placed on the inner surface of the gripper in order to assess contact with the heart surface and depth of ablation lesion.

In one embodiment of the gripper, an optical fiber with or without a lens is placed on the inner surface of the gripper in order to assess positioning and contact. The optical fiber is attached to a camera outside of the body. In one embodiment illustrated in FIG. 14B a miniature camera 91 is placed on the inner or other surface of the gripper in order to assess positioning and
15 contact.

The probe 92 of the electrode system 90 is formed from a non-conductive, flexible, adjustable material. Suitable materials for the probe include but are not limited to Pebax, polyethylene, polyester, polyurethane, silicone and Teflon. The probe may be formed of shape memory materials, for example, nitinol. The probe may be enclosed within a sheath
20 dimensioned for insertion through a small orifice. After the probe is inserted, the sheath is removed and the probe assumes a pre-formed shape. As illustrated in FIGS. 10A-J, the probe comprises a cross section defined by the probe surfaces, at least one surface being a contact surface. As illustrated in FIG. 10C or 10F, in one embodiment, the cross section of the probe may be substantially D-shaped. In other embodiments shown in FIGS. 10A-J, the cross section

- 14 -

of the probe may be circular, semi-circular, rectangular, V-shaped, D-shaped or the cross section may have multiple radii.

The electrode system 90 includes one ablator or a plurality of ablaters. The one or more ablaters 68 positioned on the probe 92 is arranged in any array, such as a linear array. The
5 spacing between ablaters 68 depends on the geometry of the cardiac tissue to be ablated. The number of ablaters, position of the ablaters, and dimension of the ablaters depend on the geometry of the cardiac tissue to be ablated, the surface of the probe on which the ablaters are placed and the requirements for probe flexibility. In one embodiment, as illustrated in FIG.15, multiple ablaters 68 are arranged in a linear array along one contact surface of the probe 92, the
10 probe 92 having a substantially rectangular cross section. In other embodiments as illustrated in cross section of FIG. 10A, a single long ablator or multiple continuous or discontinuous ablator elements may be longitudinally disposed on one semicircle of a probe the probe having a substantially circular cross section. In still other embodiments as illustrated in FIGS. 10C-J, the ablaters may be positioned around the circumference of the probe, around three sides of a
15 substantially D-shaped probe, as multiple points, or around one to three sides of a substantially rectangular probe.

In one embodiment, each ablator is attached to a low resistance conductor wire threaded through holes in the probe. In another embodiment the ablating energy of each ablator is individually controllable.

20 Each ablator is connected to a low resistance conductor wire. Energy may be delivered to one or more of these ablaters at one time (simultaneous energy delivery) or energy may be delivered sequentially. Energy delivery may be delivered in a repetitive and sequential manner e.g. x ms for electrode 1, y ms for electrode 2, z ms for electrode 3, and so on, followed again by x ms for electrode 1, y ms for electrode 2, z ms for electrode 3 and so on where x, y and z

- 15 -

are real numbers. The time between energy delivery between electrodes n and $n + 1$ may be 0 ms or a value greater than 0 ms.

Activation of the electrode energy delivery may be achieved by a control box which is manually activated or activated by an electronic control. A microprocessor may be used to
5 activate energy delivery.

One or more optical fibers may be organized in a linear (one or more rows) or curvilinear array or other geometric pattern such as an oval along the inner surface of the gripper. These may be individually or simultaneously activated with laser energy.

In one embodiment of the electrode system 90 as shown in FIG. 16A, the ablators 68 are
10 cooling elements. The probe 92 of the electrode system 90 includes an interior lumen 72, the proximate end 24 of the lumen 72 in communication with a connection port in the handle (not shown) as is known to one skilled in the art. The lumen 72 communicates with a hollow cavity 78 formed in the ablator. Cooling may be accomplished by the delivery of a fluid or gas to the
15 ablators contained within the probe. The cooling fluid may recirculate (FIG. 16A) or exit via small holes in the device. Cooling is achieved by delivering fluid or gas to the arms via one or more tubes 74. It may exit via one or more tubes 75 as shown in FIG. 16B. The fluid or gas may come in direct contact with the ablators or be separated from the ablators by a surface. This surface may be thermally conductive or non conductive. The cryoablation device may consist of one or more elements consisting of a delivery tube for the entrance of the cryogen. There are one
20 or more small orifices 69. At these orifices 69 the cryogen passes from a high to low pressure creating the cooling. In the embodiment shown in FIG. 16B there may be a pressure change only or a phase change. In the embodiment shown in FIG. 16A there is no pressure change.

In another embodiment, the ablators 68 are lasers. In one embodiment shown in FIG. 17A, the laser ablators 80 are disposed along the inner surface of the probe in an array, such as a

- 16 -

linear array. The lasers 80 are attached to conductor wire 82 leading to an energy source 84. In another embodiment illustrated in FIG. 17B, the laser ablaters 80 are lenses 86 attached by fiber optics 88 to a laser source. In another embodiment shown in FIG. 17C the laser ablaters are optical fibers attached to a laser source.

5 In one embodiment (not shown) the ablaters are ultrasound transducers. The ablaters in another embodiment are made of platinum. In one embodiment, the platinum is about 0.2-5 mm thick and about 1-5 mm long. In another embodiment, the platinum is about 2 mm thick and about 4 mm long.

The ablaters of the electrode system provide ablating energy from any energy source
10 known in the art including, but not limited to, radio frequency energy, laser energy, direct current, or ultrasound. In another embodiment the ablaters may use low temperatures, achieved by cryogenics, for example, to ablate cardiac tissue.

In one embodiment of the electrode system shown in FIG. 18A and B, the loop of the probe may be adjusted by a pull-string 94 disposed in a channel 102 within the probe 92.
15 Moving the end 98 of the pull-string 94 in the direction of the arrow 96 shown in FIG. 18A, substantially closes the probe loop as shown in FIG. 18B. In another embodiment, as illustrated in FIG. 18C, the pull-string 94 is attached to the end 120 of probe 92, and passes through a collar 126. Moving the end of the string 94 in the direction of the arrow 96, adjusts the size of the probe loop. In another embodiment shown in FIG. 19 the probe is comprised of an elastomeric
20 material for adjusting the size and dimensions of the loop. In yet another embodiment shown in FIG. 20 of the electrode system 90, the size and dimensions of the loop is adjusted by springs 100 or elastic material interposed between ablaters 68 on the probe 92 surface.

In another embodiment, attachment devices may be in communication with the probe, for example, a gripping device, such as a suction device. The probe may have one or more

- 17 -

suction elements. The suction device consists of a small hole which is located along the contact surface of the probe. This hole is attached to a tube which exits from the probe. Suction is achieved by creating negative pressure within this tube using an apparatus outside the body. In another embodiment these suction elements consist of suction cups which create suction when
5 contact pressure is applied.

In still another embodiment, the electrode system comprises a glove having at least one ablator on a probe, the probe being in communication with the finger on the glove. In another embodiment the probe and ablaters may be in communication with multiple fingers of the glove. The ablaters are placed on one or more surfaces of the glove. The ablaters may be arranged in a
10 linear or curvilinear array. These ablaters may be on the inner or outer surface of the curvature of the glove. For example, electrical ablator conductor wires are attached to the ablaters and exit from the glove to the energy source. In another embodiment using lasers, optical fibers are positioned on the surface of the glove and exit from the glove to the laser source. In another embodiment using cryoablation, the individual or single cryoablation probe or elements are
15 attached to surface of the glove and exit from the glove to the source of the cryogen.

In one embodiment, the electrode system is sized and shaped for insertion through an endoscope or thoracoscope.

The gripper and the flexible electrode are used to create myocardial ablative lesions from the epicardial and/or endocardial surface of the heart. These devices are placed in contact with
20 the epicardial surface of the heart and energy is delivered. Contact is maintained because of the shape of the device and the ability of the device to conform to and be stabilized on the epicardial surface of the heart via friction, or suction.

Another aspect of the invention comprises a system for detection of ablaters localized on endocardial ablating catheters and related devices. The ablator detection system 101, illustrated

- 18 -

in FIG. 21, comprises a detector 106 at the epicardial surface 20, at least one indicator 104, at least one ablator 68, an endocardial catheter 108 adjacent the endocardial surface 22 and an epicardial probe 110. In another embodiment the detector 106 is present adjacent to the endocardial surface 22 and the indicator 104 is on the epicardial probe 110.

5 Referring again to FIG. 21, a system 101 for detection of endocardial ablators localized on endocardial ablating catheters 108 includes an indicator 104 localized adjacent an ablator 68 positioned on the endocardial catheter 108 and a detector 106. The indicator 104 transmits signals indicating the position of the ablator 68 on the ablating catheter 108 inserted into a heart chamber 112. A detector 106 positioned on an epicardial probe 110 detects the position of the
10 endocardial indicator 104 adjacent the ablator 68 on the endocardial catheter 108. When the ablator 68 is appropriately aligned with the cardiac tissue to be ablated as detected by the epicardial detector, ablating energy is applied to ablate myocardial tissue through the endocardium 22. In another embodiment the detector 106 is on the endocardial catheter 108 and the indicator 104 is on the epicardial probe 110.

15 In one embodiment, the indicator 104 and/or the detector 106 is a magnet. A magnet may be present within or attached to the endocardial catheter and the epicardial probe. In another embodiment either the endocardial catheter or epicardial probe have a magnet and the other element has a metal attracted by a magnet. The magnet may be a natural magnet or an electromagnet. The polarities of the magnets are selected so that the endocardial and epicardial
20 magnets metal or elements attract. The endocardial catheter or epicardial probe may be positioned so that they are precisely aligned by using one or more magnets with each element.

In another embodiment, the indicator is a light source, for example, laser light. In one embodiment, there is no detector on the epicardial surface. The light is seen by the operator visually. In another embodiment there is an optical fiber on the epicardial probe to detect the

- 19 -

light from the indicator. The optical fiber may be connected to a video camera. In another embodiment a miniature video camera is placed on the epicardial probe. The light source on the catheter may be circumferential or only on one surface of the catheter. In one embodiment, the light source is on only one surface and the electrode or energy elements are only on the same surface to permit alignment. The detector 106 is positioned on an epicardial probe 110. The probe 110 is sized to fit a hand, formed from a flexible, inert substrate and dimensioned to abut an epicardial surface. In one embodiment, probes may be cylindrical and held like a pen with the interfacing region positioned at the end of the probe. In another embodiment, the probe may be rectangular or cylindrical with the interfacing region positioned on the side of the probe. In one embodiment, the detector is a magnetic field detector. Alternatively, in another embodiment the detector is a light detector. In still another embodiment the detector is an ultrasound device or an echocardiograph. In one embodiment the ultrasound is used to detect contact with cardiac tissue and depth of lesion ablation.

In one embodiment ablators are present only on the endocardial catheter or the epicardial probe. The endocardial catheter or epicardial probe are used for positioning and orientation. In one embodiment the endocardial catheter is oriented so that ablation, for example laser ablation, is directed towards the epicardial surface (FIG. 22). In one embodiment the indicator is only on one surface, the surface of the ablation elements.

The endocardial catheter is any endocardial ablating catheter known in the art.

In a clinical application of the ablator detection system, the endocardial ablating catheter is passed through a patient's artery or vein into the heart to the site of arrhythmogenic tissue. Simultaneously, the epicardial detector probe is placed by the surgeon on the epicardial surface of the heart. The indicator positioned adjacent to the ablator on the endocardial catheter transmits signals across the myocardium to the epicardial surface. The signals transmitted by the

- 20 -

indicator are detected by the detector on the epicardial probe thereby localizing the position of the endocardial ablator relative to the epicardial surface. The position of the endocardial ablator is adjusted in accordance with its relative position on the epicardial surface and the therapeutic objectives of cardiac ablation. When the endocardial ablator is determined to be appropriately
5 positioned, ablating energy is applied to cause trans-myocardial ablation.

An epicardial ultrasound imaging probe of dimensions suitable to be inserted in a thoracoscope is used to visualize the anatomy of the heart tissue from the epicardial surface to provide ablation (FIG. 23).

- 21 -

WHAT IS CLAIMED IS:

- 1 1. A gripper device for cardiac ablation comprising:
2 at least one moveable arm having an inner and outer surface; and,
3 one or more ablators disposed on said inner surface of said moveable arm.
- 1 2. The gripper device of claim 1 wherein said ablator comprises a direct current electrode.
- 1 3. The gripper device of claim 1 wherein said ablator comprises a radio frequency
2 electrode.
- 1 4. The gripper device of claim 1 wherein said ablator comprises an ultrasound transducer.
- 1 5. The gripper device of claim 1 wherein said ablator comprises a laser.
- 1 6. The gripper device of claim 1 wherein said ablator comprises a cryogenic probe.
- 1 7. The gripper device of claim 1 wherein said plurality of arms is dimensioned for
2 insertion through an endoscope.
- 1 8. The gripper device of claim 1 wherein said device is dimensioned for
2 insertion into a catheter.
- 1 9. The gripper device of claim 1 wherein said inner surface of at least one of said
2 arms is serrated.
- 1 10. The gripper device of claim 1 wherein said ablator is serrated.
- 1 11. The gripper device of claim 1 wherein at least one of said arms is dimensioned
2 and shaped to grip the epicardial circumference.
- 1 12. The gripper device of claim 1 wherein said one or more ablators are disposed along said
2 at least one arm in a geometric pattern.
- 1 13. The gripper device of claim 1 wherein said ablator comprises a linearly disposed
2 plurality of electrodes.
- 1 14. The gripper device of claim 3 wherein said ablator comprises a linearly disposed
2 plurality of electrodes.
- 1 15. The gripper device of claim 1 wherein said ablators comprise one or more optical fibers
2 connected to a laser source.
- 1 16. The gripper device of claim 1 wherein the device is made of shape memory materials.
- 1 17. The gripper device of claim 1 wherein an ultrasound imaging probe lies on the inner
2 surface of the gripper.
- 1 18. The gripper device of claim 1 wherein a miniature video camera or optical imaging fiber

- 22 -

- 2 lies on the inner surface of the gripper.
- 1 19. The gripper device of claim 1 wherein said ablator is located on at least two of
2 said arms.
- 1 20. A method for epicardial ablation comprising the steps of:
2 gripping said epicardial surface with a gripper device comprising
3 a plurality of arms, each arm having an inner and an outer surface, wherein
4 at least one of said arms is moveable; and, an ablator wherein
5 said ablator is disposed on said inner surface of at least one
6 of said moveable arms; and
7 applying said ablator to said epicardium such that cardiac conductive
8 tissue is ablated.
- 1 21. The method of claim 20 wherein said step of applying said ablator comprises
2 applying radio frequency energy to said ablator.
- 1 22. The method of claim 20 wherein said step of applying said ablator comprises
2 applying DC current to said ablator.
- 1 23. The method of claim 20 wherein said step of applying said ablator comprises
2 applying a cryogenic fluid to said ablator.
- 1 24. The method of claim 20 wherein said step of applying said ablator comprises
2 applying laser energy to said ablator.
- 1 25. The method of claim 20 wherein said step of applying said ablator comprises applying
2 ultrasound energy to said ablator.
- 1 26. An electrode system for epicardial ablation comprising:
2 a probe comprising,
3 an adjustable, flexible substrate, forming a substantially closed loop, the probe
4 having a cross section and at least one contact surface; and
5 at least one ablator located on the at least one contact surface of the probe,
6 wherein the loop is sized to substantially encompass a structure of the heart.
- 1 27. The electrode system of claim 26 wherein the loop is sized to substantially
2 encompass an epicardial structure.
- 1 28. The electrode system of claim 26 wherein said ablator on said probe is positioned on at
2 least two of said contact surfaces.

- 23 -

- 1 29. The electrode system of claim 26 wherein the cross section of the probe is substantially
2 D-shaped and the at least one ablator is positioned substantially on the flat surface
3 of the D-shaped cross section.
- 1 30. The electrode system of claim 26 wherein the cross section of the probe is substantially
2 circular and said ablator is positioned on one semicircle of the circular cross
3 section.
- 1 31. The electrode system of claim 26 wherein the cross section of the probe is rectangular
2 and the at least one ablator is positioned on the at least one surface of the
3 rectangular cross section.
- 1 32. The electrode system of claim 26 wherein said at least one ablator comprises a plurality
2 of ablators, and each of said plurality of ablators is individually actuateable.
- 1 33. The electrode system of claim 26 wherein said probe further comprises a first end and a
2 second end, wherein the diameter of said loop is adjusted by a pull-string attached
3 to one end of said probe.
- 1 34. The electrode system of claim 26 wherein the at least one ablator comprises a plurality of
2 ablators and elastic elements interspersed between and connecting pairs of the
3 plurality of ablators.
- 1 35. The electrode system of claim 26 wherein said probe is removably connected to a handle.
- 1 36. The electrode system of claim 26 wherein said at least one ablator is a direct current
2 electrode.
- 1 37. The electrode system of claim 26 wherein said ablator is a radio frequency electrode.
- 1 38. The electrode system of claim 26 wherein said ablator is an ultrasound transducer.
- 1 39. The electrode system of claim 26 wherein said ablator is a laser source.
- 1 40. The electrode system of claim 26 wherein said ablator is a cryogenic probe.
- 1 41. The electrode system of claim 26 wherein said probe is dimensioned for insertion through
2 an endoscope.
- 1 42. The electrode system of claim 26 wherein said probe is dimensioned for insertion through
2 a thoracoscope.
- 1 43. The electrode system of claim 26 wherein at least one of said contact surfaces of said
2 probe is serrated.
- 1 44. The electrode system of claim 26 wherein said adjustable flexible substrate comprises an

- 24 -

- 2 elastic material.
- 1 45. The electrode system of claim 26 wherein said probe further comprises a cooling system
2 in communication with said contact surface of said probe.
- 1 46. The electrode system of claim 26 wherein said probe further comprises an attachment
2 device in communication with said contact surface of said probe.
- 1 47. The electrode system of claim 46 wherein said attachment device comprises a suction
2 device in communication with said contact surface of said probe.
- 1 48. The electrode system of claim 46 wherein said attachment device comprises a gripping
2 device in communication with said contact surface of said probe.
- 1 49. An electrode system comprising:
2 a glove; and,
3 a probe comprising an adjustable, flexible substrate, the probe having a cross
4 section and at least one contact surface; at least one ablator located on the at least
5 one contact surface of the probe, wherein said probe is in communication with
6 said glove.
- 1 50. The electrode system of claim 49 wherein said probe is in communication with at least
2 one finger.
- 1 51. A method for epicardial ablation comprising the steps of:
2 applying to the epicardium an adjustable, flexible substrate forming a
3 substantially closed probe, and having an inner surface; and, at least one ablator
4 located on the inner surface of the probe, wherein the probe is sized to
5 substantially encompass a structure of the heart; and
6 ablating tissue within said structure of the heart.
- 1 52. A method for epicardial ablation comprising the steps of:
2 providing a glove comprising at least one ablator located on said glove;
3 gripping the heart with said glove; and
4 ablating cardiac tissue with the ablator located on said glove.
- 1 53. An electrode system for epicardial ablation comprising:
2 a probe comprising an adjustable, flexible substrate forming a substantially closed
3 loop, the probe having a cross section and at least one contact surface; and,
4 a plurality of ablators located on the at least one contact surface of the probe, wherein

- 25 -

each of the plurality of ablaters is removably attached to the substrate; and, wherein the loop is sized substantially to encompass a structure of the heart.

54. A system for detecting the relative epicardial location of an endocardial ablator comprising:

an ablator position indicator located on an endocardial device; and,
a detector located on an epicardial probe, wherein said ablator position indicator indicates the endocardial location of the ablator and the position detector detects the position of the ablator position indicator in response thereto, thereby localizing the endocardial ablator.

55. A system for detecting the relative epicardial location of an endocardial ablator comprising:

an ablator position indicator located on an endocardial device; and,
a position detector located on an epicardial probe, wherein the ablator position indicator transmits a signal and the position detector receives the signal transmitted by the ablator position indicator indicating the location of the endocardial ablator.

56. The system of claim 54 wherein the indicator comprises a magnet.

57. The system of claim 54 wherein the detector comprises a magnetic field detector.

58. The system of claim 54 wherein the indicator and detector comprise electromagnets.

59. The system of claim 55 wherein the indicator is a radiofrequency signal and the detector is a radiofrequency detector.

60. A system of claim 55 wherein the indicator is only on one surface.

61. The system of claim 55 wherein the indicator is a light transmitter and the detector comprises a light detector.

62. The system of claim 55 where in the indicator comprises a transmitter of laser light.

63. The system of claim 55 wherein the indicator comprises a light source emitting fluorescence.

64. The system of claim 55 wherein the detector comprises an echocardiograph.

65. A method for detecting the position of an endocardial ablation device and for transmyocardial ablation comprising the steps of:

indicating the position of an endocardial ablator with an indicator located on an endocardial device;

detecting the position of the indicator with a detector located on an epicardial probe,

- 26 -

4 wherein the detector detects the position of the indicator thereby localizing the endocardial
5 ablator; and,

6 applying transmyocardial ablation.

1 66. The system of claim 54 wherein the detector comprises a magnet.

1 67. The system of claim 54 wherein the detector comprises a magnet and the indicator
2 comprises a metallic element.

1 68. The system of claim 54 wherein the indicator comprises a magnet and the detector
2 comprises a metallic element.

1/13








FIG. 1
PRIOR ART:
LEFT SIDE OF HEART: SAGITTAL SECTION

2/13



3/13



4/13




FIG. 5A











FIG. 5B

5/13



6/13



7/13




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 10G




FIG. 10H




FIG. 10I




FIG. 10J

8/13




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12C




FIG. 12B




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15

10/13




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17C




FIG. 17B

11/13




FIG. 18B

FIG. 18A




FIG. 18C

12/13




FIG. 20




FIG. 19

13/13

